



MATERIAL SAFETY DATA SHEET

PRIMEPLUS 5W-30

MSDS: No 102
24-HOUR EMERGENCY NUMBERS: 800-634-4615, 800-346-5783
VERSION: No: 1
DATE: 12/1/2007
CUSTOMER SERVICE: 800-634-4615

National Fire Protection Association		HMIS Rating	
0	Health	Health	0
1	Flammability	Flammability	1
0	Reactivity	Reactivity	0
0	Special	Special	0



PROTECTIVE EQUIPMENT:

SECTION 1 – CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: PrimePlus 5W-30

Chemical Name: Motor Oil

Chemical Family: Blend

Chemical Formula: Mixture

Product Code: 101

CAS Registry: Mixture

Other Designations: None

General Use: Engine Oil.

Manufacturer: Prime Lube, Inc. P.O. Box 539 Carteret, NJ 07008 Phone (800) 634-4615
(Hours of operation: Mon-Fri 7:00am-5:00pm EST)



MATERIAL SAFETY DATA SHEET

PRIMEPLUS 5W-30

SECTION 2 – COMPOSITION / INFORMATION ON INGREDIENTS

EXPOSURE GUIDELINES			OSHA			ACGIH		
Component/CAS Number	LO%	HI%	TWA	STEL	TWA	STEL	UNIT	
Limits for the Product			5		5		MG/M3	
Severely Solvent Refined Heavy Paraffinic Petroleum Oil								
64741-88-4	.00	80.00	5		5		MG/M3	
Ethylene Propylene Copolymer								
9010-79-1	10.00	15.00		NO SPECIFIC LIMIT				
Zinc Dialkyl Dithiophosphate								
68649-42-3	2.0	2.0		NO SPECIFIC LIMIT				
Borated Polyisobuten YL Succinic Anhydride								
	0.0	10.0		NO SPECIFIC LIMIT				
Acrylic Copolymer								
68171 -46-0	0.0	1.0		NO SPECIFIC LIMIT				
Hydrotreated Heavy Paraffinic Petroleum Oil								
64742-54-7	0.0	85.0					MG/M3	
Alkyl Diphenylamine								
27177-41-9	0.0	1.0		NO SPECIFIC LIMIT				
Polybutene								
9003-29-6	0.0	1.0		NO SPECIFIC LIMIT				
Additional Exposure Limits						Government Regulation		
OTHER LIMIT – OIL MIST: 5MG'M3						OSHA PEL'ACGIH TLV		

SECTION 3 – HAZARDOUS IDENTIFICATION (HMIS)

Health: 0
Flammability: 1
Reactivity: 0
Special: 0

HMIS
H #0
F #1
R #0
PPE (Sec. 8)

0 = minimal, 1= slight, 2=moderate, 3= serious, 4= severe

EMERGENCY OVERVIEW MAY CAUSE SKIN IRRITATION

APPEARANCE: AMBER FLUID

ODOR: MOTOR OIL ODOR

POTENTIAL HEALTH EFFECTS:

INHALATION: NO EFFECTS EXPECTED

INGESTION: PRACTICALLY NON-TOXIC

EYE CONTACT: EXPECTED MINOR EYE IRRITANT

SKIN CONTACT: PRACTICALLY NON-TOXIC IF ABSORBED (LD50>2000 MG' KG).

MAY CAUSE MODERATE IRRITATION WITH PROLONGED OR REPEATED CONTACT.



MATERIAL SAFETY DATA SHEET

PRIMEPLUS 5W-30

SECTION 4 – FIRST AID MEASURES

Emergency and First Aid Procedures:

Eye contact: Flush eyes with large amounts of water for at least 15 minutes. If irritation persists, obtain medical attention.

Skin contact: Wash affected area thoroughly with soap and water until no odor remains. If redness or swelling develops, obtain medical assistance. Wash clothing before reuse.

Ingestion: Practically non-toxic. Induction of vomiting not required. Obtain medical emergency medical attention. Small amounts which accidentally enter mouth should be rinsed out until taste of substance is no longer detected.

Inhalation: Move to fresh air.

Note to Physicians: Treat symptomatically

Special Precautions/Procedures: None known

SECTION 5 – FIRE-FIGHTING MEASURES

Extinguishing Media: Water spray, dry chemical, carbon dioxide (CO₂), foam.

Flash Point: 383 °F Minimum, 195 °C Minimum

Flash Point Method: Cleveland Open Cup

Auto Ignition Temperature: 675 °F (Estimated)
359 °C (Estimated)

Flammable (Explosive) Limits (% by volume in air): Lower: Not Applicable
Upper: Not Applicable


Flammability Classification: Not Flammable

Fire-Fighting Instructions: This material will burn although it is not easily ignited. For fires involving this material, do not enter any confined space without proper PPE, including an SCBA.

Fire-Fighting Equipment: Fire may produce toxic thermal decomposition products; wear an (SCBA).

Hazardous Combustion Products: Highly dependent on combustion conditions. A complex mixture forms when this material undergoes combustion. Examples: carbon dioxide, water vapor, unidentified organic compounds.

NFPA



SECTION 6 – ACCIDENTAL RELEASE MEASURES

Spill/Leak Procedures: Recover usable material by convenient method; residual may be removed by wipe or wet mop

Small Spills: Small spills should be absorbed with a suitable inert material (sand, earth, clay, etc.). Remove the absorbed material and place in an appropriate chemical waste container for disposal.

Large Spills: For large spills, dike and pump into suitable containers. Clean up residual with suitable inert material.

Containment: For large spills, dike far ahead of liquid spill for later disposal.

Regulatory Requirements: Follow applicable Federal, State and Local regulations.

SECTION 7 – HANDLING AND STORAGE

Precautionary Measures: Keep out of reach of children.

Static Hazard: Electrostatic charge may accumulate and create a hazardous condition when handling this material. To minimize this hazard, bonding and grounding may be necessary but may not, by themselves, be sufficient.

Storage Requirements: NFPA Class IIIB Storage.



MATERIAL SAFETY DATA SHEET

PRIMEPLUS 5W-30

SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

General Considerations: Consider the potential hazards of this material (see Section 3), applicable exposure limits, job activities, and other substances when designing engineering controls suitable for the workplace.

Engineering Controls: Use in a well ventilated area.

Protective Clothing/Equipment: Skin: No special protective clothing is normally needed.

Eye/Face: No special eye protection is normally needed.

Respiratory Protection: No respiratory protection is normally needed.

Work and Hygienic Practices: Wash or rinse hands before touching eyes or contact lenses, and before eating.

Safety Stations: Make emergency eyewash stations, safety/quick -drench showers, and washing facilities available in work area.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

Appearance and odor:	Amber Fluid, Motor Oil Odor
Evaporation Rate:	1000X Slower (ETHYL ETHER=1)
Boiling Point:	High
Vapor Pressure:	<0.0001 (MM HG @ 20°C)
Pour Point, °C:	-34 (Estimated)
Specific Gravity (water =1):	0.86 (Estimated)
API Gravity:	31.0 (Estimated)
Viscosity @ 100 °C, cSt:	9.79 (Estimated)
Viscosity @ 40 °C, cSt:	65.67 (Estimated)
Vapor Density (Air =1):	>1
Solubility:	Soluble in hydrocarbons; almost completely insoluble in water
Molecular Weight:	N/A (G/MOLE)
Melting Point:	N/A
Viscosity:	55.1 SUS @ 210°F 54.5 CST @ 40°C
Packing Density:	N/A
Octanol / Water Coeff.:	N.D.
Odor Threshold:	N.D.
Vapor Density:	10+ (Air = 1)



MATERIAL SAFETY DATA SHEET

PRIMEPLUS 5W-30

SECTION 10 – STABILITY AND REACTIVITY

Stability:	Stable
Hazardous Polymerization:	Will not occur.
Materials to Avoid:	Strong oxidizing agents.
Conditions to Avoid:	Strong oxidizing agents.
Hazardous Decomposition:	Combustion will produce carbon monoxide and asphyxiants.

SECTION 11 – TOXICOLOGICAL INFORMATION

FOR THE PRODUCT –

INHALATION: Low acute toxicity.

SKIN: expected to be acutely non-toxic if absorbed. mild irritation with prolonged/repeated contact.

EYE: mildly irritating on contact.

ORAL: practically non-toxic

SEVERELY SOLVENT REFINED HEAVY PARAFFINIC PETROLEUM OIL – I

INHALATION: low acute toxicity.

SKIN: practically non-toxic if absorbed may cause moderate irritation with prolonged and repeated contact.

EYE: minimally irritating on contact.

INGESTION: Practically non-toxic if swallowed.

ETHYLENE/PROPYLENE COPOLYMER: No data available for all routes of exposure

ZINC DIALLYL DITHIO PHOSPHATE

INHALATION: Toxic hydrogen sulfide is generated when heated above 200 deg. F.

This can cause central nervous system (brain) effects, nausea, dizziness, confusion, loss of sense of smell, muscle cramps, in coordination, unconsciousness, coma, respiratory failure, or death.

SKIN: Prolonged or repeated contact may cause moderate irritation, redness, drying, cracking, dermatitis.

EYE: Irritant. ORAL: Harmful if swallowed. BORATED POLYISOBUTENYL SUCCINIC ANHYDRIDE –
No data available for all routes of exposure.

ACRYLIC COPOLYMER: No data available for all routes of exposure.

SEVERELY SOLVENT REFINED HEAVY PARAFFINIC PETROLEUM OIL: INHALATION: low acute toxicity.

SKIN: practically non-toxic if absorbed may cause moderate irritation with prolonged and repeated contact.

EYE: minimally irritating on contact.

INGESTION: Practically non-toxic if swallowed. ALKYL DIPHENYLAMINE: No data available for inhalation or eye contact.

SKIN: Possible allergic reaction. ORAL: Toxic if swallowed. May cause loss of appetite, diarrhea, & death.

POLYBUTENE: No significant effects by inhalation, skin absorption, or eye contact. ORAL: Practically nontoxic if swallowed .



MATERIAL SAFETY DATA SHEET

PRIMEPLUS 5W-30

SECTION 16 – OTHER INFORMATION

Prepared By: PRIME LUBE, INC.

Disclaimer: THE INFORMATION GIVEN HEREIN IS GIVEN IN GOOD FAITH AND FROM SOURCES WE BELIEVE RELIABLE. BUT NO WARRANTY, EXPRESS OR IMPLIED, REGARDING ITS CORRECTNESS IS MADE.

The conditions or methods of handling, storage, use and disposal of this product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of this product.

This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not apply.

CONSULT PRIME LUBE, INC FOR FURTHER INFORMATION.