



PRIME TURBINE OIL 32

APPLICATIONS

PRIME TURBINE OIL 32 is a highly refined, premium quality turbine oil developed to meet the requirements for use in large turbine systems. Prime Turbine Oil 32 provides outstanding service in circulating systems where exceptionally stable and long-life oils are needed to assure good equipment life and performance. This oil is characterized by outstanding performance in preventing rust, oxidation, foaming, air entrainment, water releasing ability and many other factors important in sophisticated turbine and bearing lubrication circulating oil systems.

ADDITIONAL FEATURES

Prime Turbine Oil 32 meets or exceeds the requirements for industrial hydraulic fluids meeting: General Electric GEK-28143A, & GEK-46506D; Denison HF-1, Cincinnati Milacron P-38, P-45, P-54, P-55, P-57, P-62; U. S. Steel 126, DIN 51524 Part 1, Mil-H-17672C, Westinghouse TLV 9013 04

TYPICAL PROPERTIES

PROPERTY	VALUE
ISO Viscosity	32
Viscosity, cSt @ 40°C	32
Viscosity, cSt@ 100°C	5.4
Color	<1.0
Demulsibility	10
Copper Corrosion, 3 hours @ 100°C	1A
Acid Number	0.15
Foam, D892	Pass
TOST Oxidation Stability (ASTM D943)	10,000

Prime Lube, Inc.
800 Roosevelt, Ave
Carteret, NJ 07008
Phone (800) 634-4615
Fax (732) 541-7999